

**SINGLE SIZE TEST PLUG (SST)**

PART NUMBER	NOMINAL PIPE SIZE	RANGE OF USE		REQUIRED INFLATION PRESSURE	MAXIMUM BACK/TEST PRESSURE	BYPASS SIZE	PRODUCT DIMENSIONS		
		MINIMUM PIPE DIAMETER	MAXIMUM PIPE DIAMETER				LENGTH	DEFLATED DIAMETER	WEIGHT
025-08	8.0" (203 mm)	6.75" (171 mm)	8.25" (210 mm)	35 psi (2.41 Bar)	15 psi (1.03 Bar)	3"	8.75" (222 mm)	6.7" (170 mm)	6.0 lbs. (2.72 kg)
025-10	10.0" (254 mm)	8.75" (222 mm)	10.25" (260 mm)	35 psi (2.41 Bar)	15 psi (1.03 Bar)	3"	10.75" (273 mm)	8.6" (218 mm)	10.0 lbs. (4.54 kg)
025-12	12.0" (305 mm)	10.75" (273 mm)	12.25" (311 mm)	35 psi (2.41 Bar)	15 psi (1.03 Bar)	3"	12.75" (324 mm)	10.4" (264 mm)	16.0 lbs. (7.26 kg)
025-15	14.0" – 16.0" (356 – 407 mm)	13.0" (330 mm)	16.25" (413 mm)	25 psi (1.72 Bar)	15 psi (1.03 Bar)	3"	16.0" (406 mm)	12.8" (325 mm)	29.0 lbs. (13.15 kg)
025-18	18.0" (457 mm)	17.0" (432 mm)	18.25" (464 mm)	25 psi (1.72 Bar)	15 psi (1.03 Bar)	3"	16.0" (406 mm)	16.0" (406 mm)	35.0 lbs. (15.88 kg)
025-21	20.0" – 21.0" (508 – 533 mm)	19.0" (483 mm)	21.25" (540 mm)	25 psi (1.72 Bar)	15 psi (1.03 Bar)	3"	16.0" (406 mm)	18.5" (457 mm)	43.0 lbs. (19.50 kg)
025-24	24.0" (610 mm)	23.0" (584 mm)	24.25" (616 mm)	25 psi (1.72 Bar)	15 psi (1.03 Bar)	3"	16.0" (406 mm)	22.0" (559 mm)	60.0 lbs. (27.22 kg)